

MODEL # WAVEPOS-55

Specification	Wavepos-55
CPU Supports	Intel Atom N270 1.6GHz
Chipset	Intel 945GSE +ICH7M
System Memory	1 x 200-pin DDR2-400/533 SODIMM Max. up to 2GB
Graphic Memory	Integrated in Intel 945GSE GEN3.5 Max. up to 224MB frame buffer sharing system memory.
LCD Touch Panel	
LCD Size	15" TFT
Brightness	250 nits
Maximal Resolution	1024 x 768
Touch Screen Type	5 Wrie Resistive Type
Tilt Angle (Degree)	0° ~ 70°
Storage	
HDD	1 x SATA 2.5" HDD Drive Bay
External I / O Ports	
PS / 2	1
Parallel port	1
USB	4 ports
RS-232 / COM	4
Audio	AC'97 Codec Audio
LAN (10/100/1000)	2 (RJ45)
2nd VGA Output	DB-15F
Control / Indicator	
Power Button	1
Power	
Power Supply	+19V DC Adaptor
Environment	
EMC & Safety	CE, FCC
Operation Temperature	0° ~ 40° C (32° ~104° F)
Storage Temperature	-20° ~ 60° C (-4° ~14° F)
Humidity	20~90%
Peripheral (optional)	
<u>Input Device</u>	
Magnetic Card Reader	3 Tracks (RS-232 / PS2 interface)
CF card reader	1
i-Button	1
<u>Output Device</u>	
Second Display	15" TFT LCD
Customer Display	VFD / LCD
Dimension (W x D x H)	(W x D x H) : 320 x 250 x 350 mm
Weight	N.W. 11 kgs